2   an information detector for detecting transmitted caller information
3   from a telephone line,

4   an operation unit for registration of caller group information which
5   relates to the transmitted caller information,

6   a memory for storing the transmitted caller information and related
7   caller group information,

8   a display unit,

9   a light source for emitting a plurality of color lights for illuminating
10 said display unit, and

11 a controller for controlling said light source,

12 wherein said light source emits a first color light when the caller
13 information detected by said information detector coincides with the caller
14 information stored in said memory and said controller causes the identification
15 and display of said caller group information, and said light source emits a second
16 color light when the caller information detected by said information detector does
17 not coincide with caller information stored in said memory .

1   6.   (Twice Amended) A telephone apparatus comprising:

2   a plurality of sub units,

3   an information detector for detecting transmitted caller information
4   from a telephone line,

5   a caller information memory for storing the transmitted caller
6   information detected by said information detector,

7   a response information memory for storing the sub unit information
8   of the sub unit answering the call and the transmitted caller information detected
9   by said information detector,

10 a sub unit specifying caller information memory for storing the sub
11 unit information and the caller information detected by said information detector

12   when the answering sub unit specifies, and

13   .   a controller,

14   wherein said controller, when detecting that the caller information

15   stored in said sub unit specifying caller information memory coincides with the

16   caller information detected by said information detector, calls a sub unit

17   corresponding to the sub unit information being read out from said sub unit

18   specifying caller information memory.